

BERJAYA DOCKYARD SDN BHD

Lot 285, Kuala Baram Industrial Estate, Kuala Baram-Brunei Border Road, 98008 Miri, Sarawak Malaysia. | Tel: +6085 605 888 | Fax: +6085 605 955 | admin@berjayadockyard.com



EFOGEN NUHA | 61.20M ANCHOR HANDLING / OFFSHORE SUPPORT VESSEL

PRINCIPAL PARTICULARS

Built : 2010 IMO Number : 9564803 Length Waterline : 61.20m

Bollard Pull : 71.68 tons with MCR 100% Depth/Draft/Scantling : 6.00m/4.50m/5.10m

Accommodation : 48 men

Classification : American Bureau of Shipping

MACHINERY/PROPULSION

Main Engine : 2 x Niigata 6MG28HX @

1838kW (2500ps) @ 750rpm

Main Generator : 3 x Caterpillar 3406C DITA

245kW @ 1500rpm

Gear Box : Twin Disc MGRP 3644AVC,

3.55:1

Tail Shafts : Forged steel propeller shaft &

intermediate shafts (grade 2)

Emergency Generator : 1 x Cummins 6BTA5.9 G1-1,

80kW @ 1500rpm

Bow Thruster : TCB-90DSMA, 8.0t CPP type

thruster powered by shaft

alternator

Stern Thruster : TCB-70DSMA, 6.0t CPP type

thruster powered by shaft

alternator

CARGO CAPACITY

Clear Deck Area : 370m²

Fuel Oil Capacity : Approx. 550.10m³
Fresh Water : Approx. 382.60m³
Mud Tank : Approx. 245.80m³
Water Ballast Tank : Approx. 471.70m³

DECK EQUIPMENTS

Anchor Windlass : Electro-hydraulic, 10t @

15m/min c/w double gypsy and single split drum with break holding 100mt (1st layer static) c/w drum capacity 100m x 96mm dia. with drum pull (1st

layer) 10t x 10m/min

Anchor & Chain : 2 x Stockless anchor 1575kg +

330m + 38mm grade U2 stud

link chain

Vertical Capstan : 2 x Electro-hydraulic, 10t @

15m/min with warping end of

380mm diameter

Tugger Winch : 2 x Electro-hydraulic, 10t @

15m/min, drum capacity 200m x 20mm dia (SWR) and brake holding 15t (static, 1st layer)

Towing Winch : 1 x Electro-hydraulic, 150t @

6m/min, drum capacity 1000m x dia 58mm (SWR) and brake holding 225t (static, 1st layer)

Shark Jaws : 160t @ capacity 32-102mm dia

chain and wire rope / 300t 3.5m long x 1.5m dia and

Stern Roller : 3.5m long x 1.5m dia and designed to take 200T line pull

at 90°

Deck Crane : 1 x Electro-hydraulic, 2.0t

(provision), 1.65t (rescue boat / liferaft), hoisting speed 0-10m/min (provision), 18m/min (rescue boat / liferaft), wire rope 12mm SWR (provision), 14mm SWR (rescue boat /

liferaft)

Particulars given herein are without warranty as to accuracy and interested parties must satisfy themselves by inspection or other means of detail of the vessel.







BERJAYA DOCKYARD SDN BHD

Lot 285, Kuala Baram Industrial Estate, Kuala Baram-Brunei Border Road, 98008 Miri, Sarawak Malaysia. | Tel: +6085 605 888 | Fax: +6085 605 955 | admin@berjayadockyard.com

NAVIGATION/COMMUNICATION EQUIPMENTS

Radar : 1 x Furuno FAR-2117 – 96Nm GMDSS Unit : GMDSS A3 Radio equipment EPIRB : 1 x Sailor SE406-II GMDSS

406MHz

SART : 2 x Sailor II radar transponder

SART II (9Hz)

Echo Sounder : 1 x Furuno FE-700

Compass : 2 x Anschutz Standard 22

compass c/w NMEA / course bus booster, 2 x steering repeater located 1 each at fwd / aft console and 1 unit located at

SGR

AIS : 1 x Furuno FA-150
GPS : 1 x Furuno GP-150
Navtex Receiver : 1 x Furuno NX-700B
Speed Log : 1 x Thomas Walker & Son

4020MK2F



